

FIG. 1





FIG. 2

+






FIG. 4

-5/9




FIG. 5





FIG. 6

_		7/9	_ 700
	Α	В	C
705 ~	UINT 32	CONVERT	USE_CHECKSUMS
710 ~	UINT 32	CONVERT	USE_RESPONSE_CACHE
715 ~	UINT 32	CONVERT	MAX_CREDENTIALS
720 ~	UINT 32	CONVERT	MAX_REQUEST_SIZE
725 ~	UINT 32	CONVERT	MAX_RESPONSE_SIZE
730 —	UINT 32	CONVERT	MAX_REQUESTS
735 _	UINT 32	CONVERT	INLINE_WRITE_HEADER_ SIZE
740 ~	UINT 32	CONVERT	USE_BACK_CONTROL_ CHANNEL
745 ~	UINT 32	CONVERT	USE_RDMA_READ_ CHANNEL
750 ~	DAFS_UTF8STRING	CONVERT	FENCE_ID_STRING
755 ~	DAFS_VAR_OFFSET_ TYPE	CONVERT/LINKED	CLIENT_ID_STRING
760 ~	DAFS_VERIFIER_TYPE	COPY	CLIENT_VERIFIER
765 ~	ENTRY TERMINATOR		

FIG. 7

755



8/9

FIG. 8

